

PATENT

UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants:	Bjorn PAULSHUS et al.)	Group Art Unit No:
)	
Serial No:	09/871,608)	Examiner:
)	
Filed:	May 31, 2001)	
)	
For:	TENSION MEMBER)	Attorney Docket No.: 7822-8271

CLEAN VERSION OF ENTIRE SET OF PENDING CLAIMS

A clean version of the entire set of pending claims is enclosed in accordance with 37 CFR 1.121 (c) (3).

Each claim of the clean version of the entire set of claims begins on a separate page in order to facilitate optical scanning of the claims by the U.S. Patent and Trademark Office.

11. (New) A tension member, comprising a plurality of fiber filaments gathered into a plurality of strands in which the filaments run close together, around which strands there is provided a protective sheath, wherein between at least some of the strands and the protective sheath there are provided spacing elements, which spacing elements define an inner cavity having a cross section corresponding to, at least, approximately the total cross section of all the strands, and that each strand is coated on the exterior thereof with sheath of a material having a low friction coefficient, permitting the strands to move longitudinally in relation to one another and independently of each other.

09071509 092504
105260 80912360

12. (New) The tension member according to claim 11, wherein the sheath consists of polyethylene or polyurethane.

00971508 003504
T05000 30914860

13. (New) The tension member according to claim 11, wherein the spacing elements are provided with recesses, which recesses are adapted to the cross-sectional form of the adjacent strands.

09271508 "092504
"092504" 20372860

14. (New) The tension member according to claims 13, wherein the spacing elements are equipped with complementary locking elements or their adjoining surfaces.

09071509.002504

15. (New) The tension member according to claim 11, wherein at least one of the spacing elements comprises a material having buoyancy in water.

00074508 092504

16. (New) The tension member according to claim 11, wherein the spacing elements consist of PVC.

09971609 "092501

17. (New) The tension member according to claim 11, wherein the spacing elements consist of a material having buoyancy in water.

09074508 "092504
F05260" B09T/2660

18. (New) The tension member according to claim 11, wherein the filaments are wound at a maximum pitch corresponding to the circumference of a drum onto which the strands are to be coiled.

09371503 09371503

19. (New) The tension member according to claim 11, wherein the strands are wound at a maximum pitch corresponding to the circumference of a drum onto which the tension member is to be coiled.

00871508-002504